

# MySentio WiFi

## Description

**MySentio WiFi** 1-053-313 / S-WIFI01

*Die*The most convenient way to operate your sauna when away from home. All functions in one app.

### Innovative technology:

- Plug & Play
- WiFi dongle\*
- User-friendly control with mobile device
- The app can be downloaded for mobile devices in the Apple App Store or Google Play Store. (Demo version included)
- All functions of the connected sauna control units\*\*
- Control of temperature and humidity
- Control of infrared radiators
- Control of the coloured LED lighting
- Control of the Cabin light
- Control of the fan
- Multiple user programs
- Can also be retrofitted for existing controllers
- Low power technology

\* The WiFi dongle is connected to the control unit by means of a network cable and must be within range of your network (WLAN).

### \*\* Compatible sauna control units:

home.com4 RS485 (1-052-984 / HC4-B-RS485)

Pro B2 (1-015-455 / PRO-B2)

Pro B3 (1-015-457 / PRO-B3)

Pro C2 (1-015-448 / PRO-C2)

Pro C3 (1-015-451 / PRO-C3)

Pro D2 (1-041-288 / PRO-D2)

Pro D2i (1-041-291 / PRO-D2i)

Pro D3 (1-041-293 / PRO-D3)

Pro D3i (1-041-295 / PRO-D3i)



### Optional accessories:

- Cut-off rocker switch (SFE-xxxx)  
(rectangular: 220x400 mm 1-045-582 / SFE-220400, 350x400 mm 1-045-583 / SFE-350400 oder 500x500 mm 1-045-588 / SFE-500500, round / diameter: 350 mm 1-045-806 / SFE-D350, 450 mm 1-045-805 / SFE-D450 oder 530 mm 1-045-585 / SFE-D530)
- Doorsensor-system (1-052-722 / SAB00102)
- Doorsensor-set (1-052-723 / SAB00103)
- BUS-Converter for PRO D (BUS-CON-D)



# MySentio WiFi

## Description

### Compatible devices / functions:

	Sauna temperatur	Humidity	Infrarot (Additional output)	Color light	Light switchable	Light dimmable	Fan switchable	Fan dimmable	Heating time	User profiles
home.com4 RS485	X	X	X	X	X		X		X	X
PRO B2	X				X				X	
PRO B3	X	X			X				X	
PRO C2	X		X		X	X	X	X	X	X
PRO C3	X	X	X		X	X	X	X	X	X
PRO D2	X				X	X	X	X	X	X
PRO D2i	X		X		X	X	X	X	X	X
PRO D3	X	X			X	X	X	X	X	X
PRO D3i	X	X	X		X	X	X	X	X	X

### Technical data:

- Dimensions: 83 x 56 x 42,5 mm
- Minimum requirement WLAN 2,4GHz: 1Mbit

### AMBIENT CONDITIONS:

- Ambient temperature: -20° C to +40° C
- Protection class: IP20

### CONNECTING CABLES:

- Ethernet cable: 8 Polig RJ45 max.30m



# MySentio WiFi

## Details

**MySentio Wifi** 1-053-313 / S-WIFI01

*Die komfortabelste Art und Weise Ihre Sauna von unterwegs zu bedienen. Alle Funktionen in einer App*

### Innovative Technik:

- Plug & Play
- WiFi Dongle\*
- Nutzerfreundliche Steuerung mit einem mobilen Endgerät
- Die App kann für mobile Geräte im Apple App Store oder Google Play Store heruntergeladen werden. (Inklusive Demo Version)
- Steuerung aller Funktionen der angeschlossenen Saunasteuerung\*\*
- Steuerung von Temperatur und Feuchte
- Steuerung der Infrarotstrahler
- Steuerung des LED Farblichts
- Steuerung des Kabinenlichts
- Steuerung des Ventilators
- Mehrere Benutzerprogramme
- Für bestehende Steuerungen nachrüstbar
- Low Power Technologie

\* Der WiFi Dongle wird mittels Netzwerkabel an die Steuerung angeschlossen und muss sich in der Reichweite Ihres Netzwerkes (WLAN) befinden.

### \*\* Kompatible Saunasteuerungen:

home.com4 RS485 (1-052-984 / HC4-B-RS485)

Pro B2 (1-015-455 / PRO-B2)

Pro B3 (1-015-457 / PRO-B3)

Pro C2 (1-015-448 / PRO-C2)

Pro C3 (1-015-451 / PRO-C3)

Pro D2 (1-041-288 / PRO-D2)

Pro D2i (1-041-291 / PRO-D2i)

Pro D3 (1-041-293 / PRO-D3)

Pro D3i (1-041-295 / PRO-D3i)



### Optionales Zubehör:

- Abschaltwippe (SFE-xxxx)  
(eckig: 220x400 mm 1-045-582 / SFE-220400, 350x400 mm 1-045-583 / SFE-350400 oder 500x500 mm 1-045-588 / SFE-500500, rund / Durchmesser: 350 mm 1-045-806 / SFE-D350, 450 mm 1-045-805 / SFE-D450 oder 530 mm 1-045-585 / SFE-D530)
- Türsensor-System (1-052-722 / SAB00102)
- Türsensor-Set (1-052-723 / SAB00103)
- BUS-Converter für PRO D (BUS-CON-D)



## MySentio WiFi

## Details

## Kompatible Geräte / Funktionen:

	Sauna-Temperatur	Feuchte	Infrarot (Zusatzaugang)	Farblicht	Licht schaltbar	Licht dimmbar	Lüfter schaltbar	Lüfter dimmbar	Laufzeit	Benutzer programme
home.com4 RS485	X	X	X	X	X		X		X	X
PRO B2	X				X				X	
PRO B3	X	X			X				X	
PRO C2	X		X		X	X	X	X	X	X
PRO C3	X	X	X		X	X	X	X	X	X
PRO D2	X				X	X	X	X	X	X
PRO D2i	X		X		X	X	X	X	X	X
PRO D3	X	X			X	X	X	X	X	X
PRO D3i	X	X	X		X	X	X	X	X	X

## Technische Daten:

- Gehäuseabmessungen: 83 x 56 x 42,5 mm
- Mindestanforderung WLAN 2,4GHz: 1Mbit

## UMGEBUNGSBEDIENUNGEN:

- Umgebungstemperatur: -20° C to +40° C
- Schutzart: IP20

## ANSCHLUSSLEITUNGEN:

- Ethernetkabel: 8 Polig RJ45 max.30m

